

PART CODE:- QCTN-R9U-HR

9U HEAT REDUCTION RACK

Q-Connect wall mount Rack is specially designed for small networking, domestic applications, audio video, telecom and networking. Its welded frame integrated with vented side walls along with an air purifier sheet. Enclosures are fabricated out of MS Steel, CNC Programmed, punched, Welded and power quoted with highest quality standard. All racks have 6 mm insulated sheets which will minimize the internal temperature by 7-10 Degrees Celsius. Also have lightning inside which will be illuminated once it opens and goes off when the door is closed.



KEY FEATURES

- Adjustable 19" equipment mounting verticals .
- Depth adjustable mounting slots.
- 2 Fans both side ventilation with air filter.
- Powder-coated finish with pretreatment process .
- Internal illumination.
- Insulated sheet to optimize temperature.

STANDARD ACCESSORIES

- Power Distribution Units
- Wire manager.
- Cantilever shelf/tray (optional).
- Fixed shelf (optional).
- Hardware packet (optional).

Technical Data

Rack Standard	Conforms to DIN 41494 or equivalent standard
Construction	Welded
Front Door	Lockable toughened glass door
Basic Frame	M S steel
Gauze	22
Equipment Mounting	DIN standard slots
Mounting Angle	19" Mounting angles made of formed steel
Standard Finish	Powder coated
Top and Bottom Cover	Welded to frame, vented, and field cable entry exit cutouts
Standard Color	Grey
Static Load	40Kgs.

